



598.00 EUR incl. 19% VAT, plus <u>shipping</u>

• STC-24850 fan-controller

## Support: Tables-Connectors

850W DC ATX P4 Power Supply (18-36VDC)

Now you can power every PC in your truck. 850W power and Pentium-4 connector are giving you all possibilities ! The ATX connector has 24 pins. Along with the power supply there is a 24pol to 20pol ATX adapter included.

| Dimensions  | 150mm[W] × 184mm[L] × 86mm[H] Standard ATX PS/2 size |
|---|--|
| Weight  | 3.5 kgs  |
| Input Voltage Range   | 18 - 36VDC   |
| Output Power<br>maximum   | 850W   |
| Output Power<br>maximum (rails)   | +3.3V : 30A  |
|   | +5.0V : 30A  |
|   | +12.0V : 60A   |
| Remote sensing  | +5V and +3.3V  |
| Over Power ProtectionLoad over 130%±10% of max. output power : shutdown |  |
| Over Voltage  | +5V, +12V & +3.3V Auto-recovery                      |
| Protection  |  |
| Short Circuit<br>Protection   | Main outputs shutdown and latch off                  |



| Over Temperature    | OTP Level is set at 110°C   |
|---------------------|---|
| Protection          | OTP Leven's set at 110 C  |
| Operating           | -20°C ~ +70°C   |
| Temperature         |   |
| Storage Temperature | -40°C~+80°C   |
| Cooling             | Build-in One 80x80x25mm Ball Bearing Fan with max. air flow 42CFM |

Note : Minimum power of 60W must be drawn at system startup time !