



339.00 EUR

incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.5Ghz
- FANLESS carpc system
- 12VDC based !

Support:  [Assembling Tutorial \[DE\]](#) |  [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.

Celeron-M 1.7Ghz is recommended for fanless operation.

| CALU specifications   |                                                                                      |
|-----------------------|--------------------------------------------------------------------------------------|
| Processor (supported) | Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher |
| Memory                | Supports DDR 333/266 DIMM RAM                                                        |
|                       | 0.8" low profile                                                                     |
|                       | 2x memory slots !                                                                    |
|                       | Maximum : 2 GB                                                                       |
| Video                 | Intel Extreme Graphics 2                                                             |
|                       | Supports up to 64MB DVMT video memory                                                |
| Audio                 | Software AC '97 Audio CODEC                                                          |
| Peripheral Connection | Front :                                                                              |
|                       | 1 x IEEE 1394 Firewire port                                                          |
|                       | 1 x USB 2.0 / 1.1 Port                                                               |
|                       | 1 x MIC Port                                                                         |
|                       | 1 x Ear Phone output Jack                                                            |
|                       | Power-on button                                                                      |
|                       | Reset button                                                                         |
|                       | Power-on and HDD LED                                                                 |
|                       | Rear :                                                                               |
|                       | 1 x RS232 COM port                                                                   |
|                       | 1 x parallel printer port                                                            |
|                       | 1 x RJ45 10/100Mb Fast Ethernet                                                      |
|                       | 1 x Line-Out output Jack                                                             |
|                       | 2 x USB 2.0 / 1.1 Ports                                                              |
|                       | 1 x 15 pin VGA                                                                       |
|                       | 1 x 12v DC Power Jack input                                                          |
| Storage               | One 2.5 inch Hard Disk and 9.5mm high.                                               |
|                       | (Support Ultra DMA 33/66/100).                                                       |
| Weight & Size         | System approximately 3kg (fully equipped).                                           |
|                       | System Dimension: 155 x 255 x 55 mm                                                  |
| Power req.            | 12V, 5A                                                                              |
| Accessory             |                                                                                      |
| Storage               | Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo                       |
|                       | Supports all 2.5" standard IDE hard drive, ATA-100/66/33.                            |

**Scope of supply**

110V/230V EU power supply

Barebone

CPU Kühlkörper

Graphics driver for 800x480 resolution : [Here](#)